3239 West 2nd Street P.O. Box 2151 Grand Island, NE 68802

Toll Free: (800) 658-0567 Phone:(308) 381-4000 Fax: (308) 381-2801



ADVISOR II

Features:

Message Slots 52 message

Cap Codes 4 individual cap Codes to allow the user to receive individual

or group pages

Character Capacity Up to 30,000 maximum character capacity

Display Optimax® EL Electra Light for easy read ability

4 lines of text with up to 8 characters per line

Message Preview Allows the user to view the first line or each message for

easy reference

Built-in Alarm Clock

Event Alarm Allows the user to set a one-time or daily alarm for up to 5

personal messages

User-Selectable Alerts Includes Vibrating, Standard, Chirping Alerts, 7 different

Selective Erase/ Erase Allows the user to ease messages individually or all at once

Graphic Battery Gauge Shows battery level

Specification:

Audio Output 78 dB @ 12"

Battery 1.5v "AA" Alkaline

Channel Spacing Wide Band

Frequency VHF (POCSAG: 143-174 MHz Flex: 163-174 MHz)

UHF (450-470) MHz 900MHz (929-932 MHz)

Operating Temperature +5°C to +40°C

Paging Protocol POCSAG or FLEX

Selectivity 55dB

Sensitivity 4.0 to 8.0 uV/M

Spurious Image Rejection 50 dB

Type Alphanumeric